

## arium<sup>®</sup> mini – Ultrapure Water System More Time for Your Research Thanks to Unique Bagtank Technology



## Bagtank Technology – Innovation for Efficient Research

Ultrapure water is the basis for every successful analysis. Yet analytical methods are becoming more and more sensitive and thus more susceptible to interference. Consistently high water quality is thus decisive for the reproducibility of results and to avoid time-consuming repeat analyses.

You can always rely on the arium<sup>®</sup> mini and its unique Bagtank system to deliver consistently high water quality that even exceeds ASTM Type 1 requirements. Because the results you achieve are more reliable, you save valuable time while increasing your efficiency.

As a pioneering and market leading manufacturer of disposable products for biopharmaceutical production, our success story continues: we have now integrated our innovative Bagtank technology into microdevices for daily laboratory use.

The closed Bagtank system reliably protects the pure water from secondary contamination by atmospheric components. Unlike conventional tank systems, the closed Bagtank system also prevents the formation of a permanent biofilm.

Depending on your needs, you can easily replace the bag (in just 5 minutes) and start always with a new basis every 6 months. This not only saves you immense effort and time spent cleaning and rinsing the system, you also avoid the use of chemicals.



## Your arium<sup>®</sup> mini Benefits

### | Reliable

Delivers consistently high water quality for reliable and reproducible results

### | Efficient

Avoids tank cleaning thanks to its unique Bagtank technology

### | Intuitive

Can be operated even with gloves via a multi-colored touch display

### | Compact

With a footprint of only 28 cm in width, it fits into any laboratory environment



## Your Requirements in the Focus – Comfortable Operation and Highest Quality Standards

In addition to the Bagtank, as our core feature we put a special focus on user-friendliness. With this in mind, we've equipped the arium<sup>®</sup>mini with a color touch screen featuring clear icons so that you can comfortably control the system – even when wearing lab gloves. This not only speeds up your workflows, it also makes them more secure thanks to active fault prevention – all in all, your daily lab work becomes easier and more efficient.

To ensure the best ultrapure water quality and the reliability of your process, we have also integrated the highest quality standards into all functional areas. For example, you can set a limit for conductivity. If this limit is exceeded, further dispensing of water will either be stopped or accompanied by a warning, as configured.

### Integrated Illumination for Easier Visual Support

- Pulsating light during water dispensing
- Impulse signals accompany error messages
- Dimmed light in standby mode

### arium<sup>®</sup> Scientific Pack for Highest Ultrapure Water Quality


- Highest cartridge capacity thanks to efficient filler materials
- Optimal flow over the resin mixed bed
- Designed for quality standard ASTM Type 1

### arium<sup>®</sup> Sterile Filter for Effective Sterility

- Validated according to HIMA and ASTM F-838-05
- Meets quality standards in accordance with USP
- Safely removes microorganisms using 0.2-µm membrane







### Intuitive Menu Navigation for Optimal User Comfort

- Icon-supported interface with touch display
- Display of current measured values and messages
- Favorites function to dispense recurring volumes

### arium® UV Lamp for Critical Analyses (185/254 nm\*)

- Optimal temperature gradient thanks to horizontal installation
- Degradation of organic components (TOC) by irradiation (<5 ppb)
- Inactivates microorganisms by damaging their DNA

### arium® Pre-treatment Cartridge for Effective Purification

- Effective adsorption using high-quality activated carbon
- Special catalyst removes oxidants
- Containment retained by reverse osmosis

## Integrated Bagtank technology – A revolution in Laboratory Water Purification

arium® mini is the only ultrapure water system with integrated Bagtank technology. The 5-liter bag developed for the ariummini is made of the proprietary material S71. Originally developed for the pharmaceutical industry, this multilayer, specialized film conforms to the biocompatibility standards of ISO and USP. Its quality and composition allows you to optimally store your pre-treated pure water for the production of Type 1 ultrapure water.

The bag is laterally integrated into the system. This enables a footprint-reducing and compact device width of only 28 cm. The system can thus be integrated into any laboratory environment almost independently of the available space. The place of installation can also be chosen flexibly.

The integrated Aqua Stop system lets you enjoy active leakage protection while ensuring maximum safety in your laboratory.





# Integrated Bagtank technology – A revolution in Laboratory Water Purification

arium® mini is the only ultrapure water system with integrated Bagtank technology. The 5-liter bag developed for the arium®mini is made of the proprietary material S71. Originally developed for the pharmaceutical industry, this multilayer, specialized film conforms to the biocompatibility standards of ISO and USP. Its quality and composition allows you to optimally store your pre-treated pure water for the production of Type 1 ultrapure water.

The bag is laterally integrated into the system. This enables a footprint-reducing and compact device width of only 28 cm. The system can thus be integrated into any laboratory environment almost independently of the available space. The place of installation can also be chosen flexibly.


The integrated Aqua Stop system lets you enjoy active leakage protection while ensuring maximum safety in your laboratory.

# Intelligent Technology – Systematic Ultrapure Water Purification

With intelligent technology the arium®mini permanently protects against secondary contamination and consistently ensures the highest water quality.

The closed Bagtank system automatically regulates pressure equalization so that no<sub>2</sub>CO can penetrate. This additionally prevents ion contamination and maintains consistently low conductivity. As an added benefit, you profit from particularly high cartridge capacity because there is less demand placed on the ion exchangers.

Moreover, you can prevent the formation of a permanent biofilm and thereby additional TOC loading. Depending on your requirements, you replace the bag every 6 months and simply start with a new basis.



## 5-liter Bag for Minimal Maintenance

- Easy bag replacement in less than 5 minutes
- No use of cleaning agents needed
- Practical and safe connection using quick connector

## Innovative Technology Prevents Secondary Contamination

- Optimum water quality by preventing permanent biofilm
- Closed system guarantees purity
- Stable quality thanks to the special high-gas barrier multilayer S71 film

## Sophisticated Power Backup Functions

- Integrated pump for increasing water pressure
- Filling arium® mini with pre-treated water: 2 minutes
- Filling arium® mini plus with RO permeate: 8 liters per hour



## Intuitive Menu Navigation for Optimal User Comfort

- Icon-supported interface with touch display
- Display of current measured value and messages
- Favorites function to dispense recurring volumes

## arium® UV Lamp for Critical Analyses (185 & 254 nm\*)

- Optimal temperature gradient thanks to horizontal installation
- Degradation of organic components (TOC) by irradiation (<4ppb)
- Inactivates microorganisms by damaging their DNA

## arium® Pre-treatment Cartridge for Effective Purification

- Effective adsorption using high-quality activated carbon
- Special catalyst removes oxidants
- Containment retained by reverse osmosis

## The Right arium® mini Version for Your Everyday Applications

### arium® mini

Standard Version – Without Direct Water Connection

The device is fed via the integrated bag, which is filled by means of a built-in pump. Pre-treated water is automatically transferred from a vessel in the bag and thus serves as feed water for the production of Type 1 ultrapure water.

### arium® mini plus

Advanced Version – with Direct Connection to the Drinking Water Supply Line

Combined with a pre-treatment stage, the device is connected directly to the potable water supply. The processed water is then produced directly into the bag. The final production of Type 1 ultrapure water is then carried out with the specially developed arium® Scientific purification cartridge.

Water Quality	arium® mini	arium® mini plus
Type 1 Water		
Type 3 Water		

Applications	arium® mini   mini plus	arium® mini UV   mini plus UV
Buffer and media preparation		
Histology		
Preparation of reagents, blank samples etc.		
ELISA (enzyme-linked immunosorbent assay)		
AAS  GF-AAS (atomic absorption spectrometry)		
Photometry		
SPE (solid phase extraction)		
IC (ion chromatography)		
LC-MS (liquid chromatography–mass spectrometry)		
GS-MS (gas chromatography coupled with mass spectrometry)		
HPLC (high-performance liquid chromatography)		

## Services available for your arium<sup>®</sup> mini

Optimize the performance of your ultrapure water system and look forward to many years of trouble-free operation by availing yourself of the professional installation, extended warranty and preventive maintenance services we offer.

Our service specialists undergo continuous and thorough training in order to guarantee you'll always receive the best possible on-site service.

- Comprehensive feedwater analysis and corresponding device configuration
- Installation and startup for quick and safe usability
- Maximum safety by extended warranty
- Extended service life through regular checks tailored to your needs







## PB-10 Basic Bench Top pH Meter

- Automatic calibration with recognition of up to 16 buffers
- Automatic temperature compensation
- Electrode check during calibration
- Stability icon
- BNC connector for glass-membrane pH electrodes or Redox electrodes



### Measuring range

Voltage:	$\pm 1500.0 \text{ mV}$
pH:	0 to + 14.00
Temperature:	- 5 to + 105°C

### Resolution

Voltage:	$\pm 0.1 \text{ mV}$
pH:	$\pm 0.01$
Temperature:	$\pm 0.1^\circ\text{C}$

### Accuracy

Voltage:	$\pm 0.4 \text{ mV}$
pH:	$\pm 0.01$
Temperature:	$\pm 0.2^\circ\text{C}$



### Operation Easy with four keys:

- pH/mV
- Standardize
- Setup
- Enter

Dimensions (W x D x H) 230x120x80 mm

Net weight approx. 2 kg

- Standard Equipment/Equipment Supplied:
- Electrode holding arm and base plate.
- pH combination Gel-filling electrode
- With integrated temperature sensor (3-in-1)
- AC adapter

## Sales and Service Contacts

For further contacts, visit [www.sartorius.com](http://www.sartorius.com)

### Europe

**Germany**  
Sartorius Lab Instruments  
GmbH & Co. KG  
Weender Landstrasse 94-108  
37075 Goettingen  
Phone +49.551.308.0  
Fax +49.551.308.3289

**France & Suisse Romande**  
Sartorius France  
2, rue Antoine Laurent de Lavoisier  
ZA de la Gaudrée  
91410 Dourdan  
Phone +33.1.70.62.50.00  
Fax +33.1.64.59.76.39

**Austria**  
Sartorius Austria GmbH  
Modecenterstrasse 2  
1030 Vienna  
Phone +43.1.7965760.0  
Fax +43.1.7965760.24

**Belgium**  
Sartorius Belgium N.V.  
Rue Colonel Bourg 105  
1030 Bruxelles  
Phone +32.2.756.06.90  
Fax +32.2.481.84.11

**Finland & Baltics**  
Sartorius Biohit Liquid Handling Oy  
Laippatie 1  
00880 Helsinki  
Phone +358.9.755.951  
Fax +358.9.755.95.200

**Hungary**  
Sartorius Hungária Kft.  
Kagyló u. 5.  
2092 Budakeszi  
Phone +3623.457.227  
Fax +3623.457.147

**Ireland**  
Sartorius Ireland Ltd.  
Unit 41, The Business Centre  
Stadium Business Park  
Ballycoolin Road  
Dublin 11  
Phone +353.1.8089050  
Fax +353.1.8089388

**Italy**  
Sartorius Italy S.r.l.  
Viale A. Casati, 4  
20835 Muggiò (MB)  
Phone +39.039.4659.1  
Fax +39.039.4659.88

**Netherlands**  
Sartorius Netherlands B.V.  
Phone +31.30.60.53.001  
Fax +31.30.60.52.917  
info.netherlands@sartorius.com

**Poland**  
Sartorius Poland sp. z o.o.  
ul. Wrzesinska 70  
62-025 Kostrzyn  
Phone +48.61.6473830  
Fax +48.61.6473839

**Russian Federation**  
LLC "Sartorius RUS"  
Uralskaya str. 4, Lit. B  
199155 St. Petersburg  
Phone +7.812.327.53.27  
Fax +7.812.327.53.23

**Spain & Portugal**  
Sartorius Spain, S.A.  
Avda. de la Industria, 32  
Edificio PAYMA  
28108 Alcobendas (Madrid)  
Phone Spain +34.902.123.367  
Phone Portugal +351.800.855.800  
Fax Spain +34.91.358.96.23  
Fax Portugal +351.800.855.799

**Switzerland**  
Sartorius Mechatronics Switzerland AG  
Ringstrasse 24a  
8317 Tagelswanger (ZH)  
Phone +41.44.746.50.00  
Fax +41.44.746.50.50

**U.K.**  
Sartorius UK Ltd.  
Longmead Business Centre  
Blenheim Road, Epsom  
Surrey KT19 9QQ  
Phone +44.1372.737159  
Fax +44.1372.726171

**Ukraine**  
LLC "Biohit"  
Post Box 440 "B"  
01001 Kiev, Ukraine  
Phone +380.44.411.4918  
Fax +380.50.623.3162

### Americas

**USA**  
Sartorius Corporation  
5 Orville Drive, Suite 200  
Bohemia, NY 11716  
Phone +1.631.254.4249  
Toll-free +1.800.635.2906  
Fax +1.631.254.4253

**Argentina**  
Sartorius Argentina S.A.  
Int. A. Avalos 4251  
B1605 ECS Munro  
Buenos Aires  
Phone +54.11.4721.0505  
Fax +54.11.4762.2333

**Brazil**  
Sartorius do Brasil Ltda  
Avenida Senador Vergueiro 2962  
São Bernardo do Campo  
CEP 09600-000 - SP - Brasil  
Phone +55.11.4362.8900  
Fax +55.11.4362.8901

**Canada**  
Sartorius Canada Inc.  
2179 Dunwin Drive #4  
Mississauga, ON L5L 1X2  
Phone +1.905.569.7977  
Toll-Free +1.800.668.4234  
Fax +1.905.569.7021

**Mexico**  
Sartorius de México S.A. de C.V.  
Circuito Circunvalación Poniente  
No. 149  
Ciudad Satélite  
53100, Estado de México  
México  
Phone +52.5555.62.1102  
Fax +52.5555.62.2942

### Asia | Pacific

**Australia**  
Sartorius Australia Pty. Ltd.  
Unit 5, 7-11 Rodeo Drive  
Dandenong South Vic 3175  
Phone +61.3.8762.1800  
Fax +61.3.8762.1828

**China**  
Sartorius (Shanghai) Trading Co., Ltd.  
3rd Floor, North Wing, Tower 1  
No. 4560 Jinke Road  
Zhangjiang Hi-Tech Park  
Pudong District  
Shanghai 201210, P.R. China  
Phone +86.21.6878.2300  
Fax +86.21.6878.2882

**Hong Kong**  
Sartorius Hong Kong Ltd.  
Unit 1012, Lu Plaza  
2 Wing Yip Street  
Kwun Tong  
Kowloon, Hong Kong  
Phone +852.2774.2678  
Fax +852.2766.3526

**India**  
Sartorius Weighing India Pvt. Ltd.  
#69/2-69/3, NH 48, Jakkasandra,  
Nelamangala Tq  
562 123 Bangalore, India  
Phone +91.80.4350.5250  
Fax +91.80.4350.5253

**Japan**  
Sartorius Japan K.K.  
4th Fl., Daiwa Shinagawa North Bldg.  
8-11, Kita-Shinagawa 1-chome  
Shinagawa-ku, Tokyo, 140-0001 Japan  
Phone +81.3.3740.5408  
Fax +81.3.3740.5406

**Malaysia**  
Sartorius Malaysia Sdn. Bhd  
Lot L3-E-3B, Enterprise 4  
Technology Park Malaysia  
Bukit Jalil  
57000 Kuala Lumpur, Malaysia  
Phone +60.3.8996.0622  
Fax +60.3.8996.0755

**Singapore**  
Sartorius Singapore Pte. Ltd  
1 Science Park Road,  
The Capricorn, #05-08A,  
Singapore Science Park II  
Singapore 117528  
Phone +65.6872.3966  
Fax +65.6778.2494

**South Korea**  
Sartorius Korea Ltd.  
8th Floor, Solid Space B/D,  
PanGyo Yeok-Ro 220, Bundang-Gu  
Seongnam-Si, Gyeonggi-Do, 463-400  
Phone +82.31.622.5700  
Fax +82.31.622.5799

**Thailand**  
Sartorius (Thailand) Co. Ltd.  
129 Rama 9 Road,  
Huaykwang  
Bangkok 10310  
Phone +66.2643.8361-6  
Fax +66.2643.8367



◀ [www.sartorius.com](http://www.sartorius.com)

**lesoshoppe.com**  
Lesoshoppe Sdn Bhd (Shah Alam)  
Elite Industrial Park,  
12, Jalan Gitar 33/3, Seksyen 33,  
40400 Shah Alam, Selangor  
Phone : +603-51212673  
Email : [enquiry@lesoshoppe.com](mailto:enquiry@lesoshoppe.com)